

**Sikadur 35 Hi-Mod LV**

Sikadur 35, Hi-Mod LV is a 2-component, 100% solids, moisture-tolerant, low-viscosity, high-strength, multi-purpose, epoxy resin adhesive. It conforms to the current ASTM C-881 and AASHTO M-235 specifications.

**Where To Use**

Pressure-injection of cracks in structural concrete, masonry, wood, etc. Grouting bolts, dowels, pins, etc. Gravity-feed of cracks in horizontal concrete & masonry. Epoxy resin binder for epoxy mortar patching & overlay of interior, horizontal surfaces. Seal interior slabs and exterior above-grade slabs from water, chlorides, and mild chemical attack; also improves wearability.

**Packaging**

3 gal units; 1 gal units, 2/case; 12 fl.-oz units, 12/case.

**Sikadur 52**

Sikadur 52 is a 2-component, 100% solids, moisture-tolerant, epoxy adhesive. It is a low-viscosity, high-strength adhesive formulated specifically for grouting both dry and damp cracks. It conforms to the current ASTM C-881 and AASHTO M-235 specifications.

**Where To Use**

Use neat for gravity feed or pressure injection of cracks in structural concrete, masonry, wood, etc. Seal interior slabs & exterior above grade slabs from water, chlorides and mild chemical attack and to improve wearability.

**Packaging**

3-gal. units.

**Sikadur Injection Gel**

Sikadur Injection Gel is a 2-component, 100% solids, moisture-tolerant, high-modulus, high-strength, structural epoxy. When mixed it gives a smooth, non-abrasive, paste adhesive. It conforms to the current ASTM C-881 and AASHTO M-235 specifications.

**Where To Use**

Structural crack repairs not exceeding 1/4 in. width. Mechanical grouting. . . bolts, dowels, pins, machine & 'robotic' base plates, bearing pads, etc. Waterproofing tunnels, cable vaults, tanks, basements, etc. Re-anchoring of veneer masonry. Wood-truss repairs. Preventive maintenance - grout large cracks on new or existing structures to seal off reinforcing steel from the elements of corrosion. Anchor grouting...bolts, dowels, pins and special fasteners. As a pick-proof sealant around windows, doors, lock-ups, etc. inside correctional facilities.

**Packaging**

4 gal. units

**Sikafix HH**

SikaFix HH is a high-solids, hydrophobic, polyurethane, liquid chemical grout. It is pumped into cracks and voids to stop water infiltration.

**Where To Use**

SikaFix permanently stops unwanted water which is infiltrating through: Defective concrete (cracked or honeycombed). Concrete joints, limestone (tunnels, dams), pipe intrusions, wastewater tanks, conduits, sewers, manholes, utility boxes, etc.

**Packaging**

5 gallon pail with 1 pint accelerator, 55 gallon drum with 11 pints accelerator. Additional SikaFix Accelerator is available in 1gal cans, 2/case & 1pt cans, 4/case. SikaFix Pump Flush is available in 5 gallon pails or 55 gallon drums. Note 5 gallon pail with 1pt accelerator=1 unit. Base Resin A & Accelerator B

**Sikapronto 19**

SikaPronto 19 is a 2-component, rapid-curing, solvent-free, high molecular weight methacrylate, crack healer/penetrating sealer.

**Where To Use**

Use on grade, above and below grade on concrete and mortar. SikaPronto 19 seals surface of concrete from water and chlorides. For horizontal decks, slabs, patios, driveways, parking garages and other substrates exposed to foot and pneumatic-tire traffic.

**Packaging**

1 gal. units, 4/ctn.; 4.5 gal. units.

**Sikadur Combiflex**

Versatile sealing system for irregular and difficult joints and cracks. Withstands extreme movements and chemical exposures while maintaining a water-tight seal. The system consists of Sikadur 31, Hi-Mod Gel, epoxy adhesive, and Combiflex perforated Hypalon® sealing strip.

**Where To Use**

Types of Joints: construction, expansion, cracks, connecting. Types of Substrates: Concrete, mortar steel, iron, aluminum, brick, wood, and other building materials. Types of Structures: tunnels, pipes, storage tanks, swimming pools, parking garages, sewage treatment tanks, and roofs.

**Packaging**

Kits: Pre-measured kits containing 4 in. wide by 20 ft. long Hypalon sheeting, 60 oz. of Sikadur 31, Hi-Mod Gel and 1 pint of Combiflex Activator. The components may be also be purchased separately: Hypalon sheeting - 4, 8 and 12in. wide by 20' long

and 12 oz. units, 12/case.

<http://www.sikaconstruction.com>

