



CONVENTIONALS

Features

Standard Equipment

- Driveable at full height
- Variable rear wheel hydraulic drive
- Dual parking brakes
- Proportional controls for drive/lift w/ joystick controller
- 3' roll out extension deck
- 24V DC power source
- Low voltage battery protection
- 25% Gradeability
- Solid rubber, non-marking tires (except 6826,6832)
- Black, foam-filled tires (6826, 6832)
- Pothole protection (except 6826, 6832)
- 110V GFI AC outlet on platform
- Tilt alarm with drive/lift cutout
- All motion alarm
- Lanyard attachment points
- Operator horn
- Hinged railing system (except 3220, 4620)
- Forklift pockets, lifting lugs / tie downs

Optional Equipment

- Flashing light
 - 6' powered deck ext. 3220
 - 6' powered deck ext. 4620, 4626
 - 5' powered deck ext. 6826, 6832
 - Shop airline to platform
 - 800 watt AC generator
 - EE rating package
 - Power Pack(LP or diesel)(except 3220,3226)
 - Kit for power pack
 - Hinged railing system - 3220
 - Hinged railing system - 4620
 - Spring loaded half height gate
 - Spring loaded full height gate*
 - Non-marking, foam-filled tires(6826,6832 only)
 - air operation package
- * not available with hinged railing system
 ** Standard lead times may be increased when optional equipment is added, consult factory

Specifications

Model	3220	3226	4620	4626	4832	6826	6832
Work Height	26'	32'	26'	32'	38'	32'	38'
Raised Plat. Height (nom)	20'	26'	20'	26'	32'	26'	32'
Lowered Platform Height	38"	45"	38"	45"	48.5"	50"	55.5"
O/A Width	32"	32"	46"	46"	48"	68"	68"
O/A Length	91.5"	91.5"	91.5"	91.5"	91.5"	99.5"	99.5"
Stowed Height (rails up)	77.5"	84.7"	79.5"	89"	92"	93.5"	99"
Stowed Height (rails down)	OPT. (63.5")	70.6"	OPT. (67.3")	73.5"	77"	78.5"	84"
% Gradeability	25%	25%	25%	25%	25%	25%	25%
Platform Size (inside dimension)	28"x84"	28"x84"	42"x84"	42"x84"	42"x84"	57"x84"	57"x84"
Capacity* Lbs	900 lb	500 lb	1,100 lb	850 lb	700 lb	1,200 lb	850 lb
Travel speed mph	2 mph	2 mph	2 mph	2 mph	2 mph	2 mph	2 mph
Lift time (sec)	33	56	36	58	64	65	60
Weight * Lbs	3,510 lb	4,135 lb	3,700 lb	4,940 lb	5,900 lb	5,380 lb	5,680 lb

* Capacities, and machine weights may differ when options are added

