



BIG DECK ELECTRICS

Features

Standard Equipment

- Driveable at full height
- Variable rear wheel electric drive
- Disk type parking brake system on rear axle
- Proportional controls for drive/lift w/ joystick controller
- 3' roll out extension deck (6826E, 6832E)
- 48V DC power source
- Low voltage battery protection
- 30% Gradeability
- 110V GFI AC outlet on platform
- Tilt alarm with drive/lift cutout
- All motion alarm
- Lanyard attachment points
- Operator horn
- Flashing light (except 6826E, 6832E)
- Hinged railing system
- Forklift pockets, lifting lugs / tie downs

Optional Equipment 6826E, 6832E**

- Flashing light
- 5' power deck extension
- Shop airline to platform
- 800 watt AC generator
- Spring loaded half height gate
- Spring loaded full height gate
- Non-marking, foam-filled tires

Optional Equipment 8831E, 8841E**

- 4' roll out deck ext. (front/rear)
- 4' powered deck ext. (front/rear)
- 4 wheel drive package
- Independent leveling hydraulic outriggers
- EE rating package
- Spring loaded full height gate
- Grip lug, foam-filled tires
- Grip lug, air-filled flotation type tires

** Standard lead times may be increased when optional equipment is added, consult factory

Specifications

Model	6826E	6832E	8831E	8841E
Work Height	32'	38'	37'	47'
Raised Plat. Height (nom)	26'	32'	31'	41'
Lowered Platform Height	50"	55.5"	59"	69"
O/A Width	68"	68"	87"	87"
O/A Length	99.5"	99.5"	137.5"	137.5"
Stowed Height (rails up)	93.5"	99"	105"	114"
Stowed Height (rails down)	78.5"	84"	78.5"	87.5"
% Gradeability	30%	30%	30%	30%
Platform Size (inside dimension)	57"x84"	57"x84"	70"x138"	70"x138"
Capacity* Lbs	1,200 lb	1,000 lb	2,500 lb	1,500 lb
Travel speed mph	2 mph	2 mph	3 mph	3 mph
Lift time (sec)	59	60	62	67
Weight * Lbs	5,860 lb	6,160 lb	10,575 lb	12,170 lb

* Capacities, and machine weights may differ when options are added



**-- NEW OR USED --
-- SALE OR RENTAL --**

