



**MID-SIZE RT's**

**Features**

**Standard Equipment**

- Driveable at full height
- Dual fuel (gas/propane) engine on roll out tray
- 4.5' roll out deck extension
- Disk brake system on rear axle
- 30% Gradeability
- 110V GFI AC outlet on platform
- Tilt alarm with drive/lift cutout
- All motion alarm
- Lanyard attachment points
- Operator horn
- Flashing light
- Hinged railing system
- Spring loaded full height gate at rear
- Grip Lug, air-filled tires

**Optional Equipment \*\***

- 4.5' powered deck extension
- 4 wheel drive package
- 3500 watt hydraulic generator
- Diesel engine (in lieu of std dual fuel)
- Diesel scrubber (only on diesel engine)
- Independent leveling hydraulic outriggers
- Shop airline to platform

\*\* Standard lead times may be increased when optional equipment is added, consult factory

**Tire options**

- Grip lug, foam-filled tires
- Grip lug, air-filled flotation type tires



**Specifications**

Model	7127	7135
Work Height	33'	41'
Raised Plat. Height (nom)	27'	35'
Lowered Platform Height	60.5"	67.5"
O/A Width	71.5"	71.5"
O/A Length	127"	127"
Stowed Height (rails up)	105.5"	112.5"
Stowed Height (rails down)	77"	84"
% Gradeability	30%	30%
Platform Size (inside dimension)	64"x116.5"	64"x116.5"
Capacity* Lbs	1,500 lb	1,000 lb
Travel speed mph	3 mph	3 mph
Lift time (sec)	31	38
Weight * Lbs	7,930 lb	8,350 lb

\* Capacities, and machine weights may differ when options are added

