



TEREX
LIGHT CONSTRUCTION

MORRISON POWER BUGGIES

Save time and money on your next job with Morrison multi-purpose power buggies. Use them for concrete spot pouring and spread dumping, construction debris removal, landscaping, material handling and distribution and on-site tool and equipment transportation. PB 10 walk-behind model has 10 cu.ft. capacity, PB 16 and PB 21 rider models have 16 cu.ft. and 21 cu.ft. capacities, respectively.



SPECIFICATIONS

	PB 10	PB 16	PB 21
Model	Walk-Behind	Rider	Rider
Wheelbase	37.5" (952.5 mm)	44" (1117.6 mm)	44" (1117.6 mm)
Overall Length	80.5" (2044.7 mm)	103" (2616.2 mm)	101.5" (2578.1 mm)
Overall Width:			
Single Wheels	29.0" (736.6 mm)	35.5" (901.7 mm)	45.25" (1149.4 mm)
Dual Wheels	39.0" (990.6 mm)	43.5" (1104.9 mm)	45.25" (1149.4 mm)
Overall Height	48.5" (1231.9 mm)	53" (1346.2 mm)	52" (1320.8 mm)
Maximum Load	1500 lbs. (680.4 kg)	2500 lbs. (1136 kg)	3200 lbs. (1455 kg)
Capacity	10 cu. ft. (283 l)	16 cu. ft. (453 l)	21 cu. ft. (595 l)
Speed	3.5 mph (5.6 km/h)	7.25 mph (11.67 km/h)	7.25 mph (11.67 km/h)
	at 4000 rpm	at 4000 rpm	at 4000 rpm
Drive	Hydrostatic	Hydrostatic	Hydrostatic
Brakes	Hydraulically Controlled	Hydraulically Controlled	Hydraulically Controlled
Dump	Variable Hydraulic	Variable Hydraulic	Variable Hydraulic
Engine	8 hp Honda	13 hp Honda	18 hp Briggs & Stratton
Operating Weight	861 lbs. (390.5 kg)	1200 lbs. (544.2 kg)	1375 lbs. (623.6 kg)
Turning Radius	60" (1524 mm)	73.5" (1867 mm)	73.5" (1867 mm)
Ground Clearance	5" (127.0 mm)	6" (152.4 mm)	6" (152.4 mm)
Discharge Height	2.5" (63.5 mm)	5" (127 mm)	6" (152.4 mm)

MORRISON HIGH FREQUENCY VIBRATING SCREEDS

Morrison screeds employ a unique patented principle that distributes high frequency vibrations evenly across the entire length of the screed. This enables the concrete finisher to produce smooth, uniform surfaces quickly and easily, even with low slump concrete. With more than 12,000 vibrations per minute, Morrison screeds perform 25% faster than competitive screeds on either high or low slump concrete.



SCREED SPECIFICATIONS

Screed Type	Height	Width	Weight (lbs./ft.)	Engine	Best Application
Standard	13-1/2"	12-1/8"	10' Base 79 lbs. 2-1/2' section 23 lbs. 5' section 45 lbs. 10' section 78 lbs. Motor w/mount 53 lbs.	5 hp Honda	Intended for spans up to 45'
Super	19-1/2"	14-5/8"	10' Base 94 lbs. 2-1/2' section 23 lbs. 5' section 46 lbs. 10' section 91 lbs. Motor w/mount 70 lbs.	8 hp Honda	Intended for spans up to 70'

