

**TAMMSWELD - 55 GALLON DRUM**Version 2.
REVISION DATE: 09/24/2008

Print Date 09/26/2008

SECTION 1 - PRODUCT IDENTIFICATION

Trade name : TAMMSWELD - 55 GALLON DRUM
 Product code : THHWD55

COMPANY : Euclid Chemical Company
 19218 Redwood Road
 Cleveland, OH 44110

Telephone : 1-800-321-7628
 Emergency Phone: : U.S. only: 1-800-424-9300
 International Users Call Collect: 1-703-527-3887

Product use : Coating

SECTION 2 - HAZARDS IDENTIFICATION**Emergency Overview**

Off-White to White. Liquid. No serious effects anticipated under normal conditions of use. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

Acute Potential Health Effects/ Routes of Entry

Inhalation : No serious effects anticipated under normal conditions of use.
 Eyes : Direct contact may cause mild irritation.
 Ingestion : May cause gastrointestinal irritation, nausea, and vomiting.
 Skin : May cause mild irritation.

Aggravated Medical Conditions

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

In animal studies, prolonged or repeated exposure to ethylene glycol (or its components) has been suggested as a cause of reproductive effects and kidney and liver damage. It has caused birth defect in animal studies at high oral doses. Prolonged and repeated to ethylene glycol (or its components) has been suggested as a cause of kidney and liver damage in humans. Ethylene glycol is not expected to cause cancer in humans, since it did not cause cancer in laboratory animals and is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA). Long term inhalation exposure to vinyl acetate at high levels (600 ppm) caused nasal tumors in laboratory animals, some of which were shown to be carcinomas. However, there is no evidence that vinyl acetate may cause cancer in humans. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

SECTION 3 - PRODUCT COMPOSITION

Chemical Name	CAS-No.	Weight %
Water	7732-18-5	> 60.0
Ethylene-Vinyl Acetate Copolymer	24937-78-8	30.0 - 60.0



TAMMSWELD - 55 GALLON DRUM

Version 2.
REVISION DATE: 09/24/2008

Print Date 09/26/2008

Ethylene glycol	107-21-1	1.0 - 5.0
Vinyl acetate	108-05-4	- <1.0

SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

- Inhalation : Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.
- Eye contact : Flush with water for 15 minutes. If irritation persists, get medical attention.
- Skin contact : Wash area of contact thoroughly with hand cleaner followed by soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
- Ingestion : Get medical attention. Do not induce vomiting.
- Notes to physician : Not applicable.

SECTION 5 - FIRE FIGHTING MEASURES

- Flash point : Not available.
- Method : Not applicable.
- Lower explosion limit : Not available.
- Upper explosion limit : Not available.
- Autoignition temperature : Not available.
- Extinguishing media : This product is not expected to burn under normal conditions of use.
- Hazardous combustion products : Carbon monoxide and carbon dioxide can form. Smoke, fumes.
- Protective equipment for firefighters : Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA).
- Fire and explosion conditions : This product not expected to ignite under normal conditions of use.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Transfer to appropriate container for disposal. Stop flow. Contain spill. Keep out of water courses. Absorb spill in sand, earth or other suitable material. Transfer to appropriate container for disposal. Use appropriate protective equipment. Avoid contact with material.

SECTION 7 - HANDLING AND STORAGE

Handle in compliance with common hygienic practices. Clean hands thoroughly after handling. Keep from freezing. Do not use in confined or poorly ventilated areas. Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Store in sealed containers in a dry, ventilated warehouse location above freezing.



TAMMSWELD - 55 GALLON DRUM

Version 2.
REVISION DATE: 09/24/2008

Print Date 09/26/2008

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Personal protection equipment

- Respiratory protection : Not required under normal conditions of use. Wear appropriate, NIOSH/MSHA approved respirator with combination particulate filter and vapor/gas removing cartridge when the ventilation is not adequate or if it is necessary to abrade or grind surfaces coated with this product.
- Hand protection : Use suitable impervious rubber or vinyl gloves and protective apparel to reduce exposure.
- Eye protection : Wear appropriate eye protection. Wear chemical safety goggles and/or face shield to prevent eye contact. Do not wear contact lenses. Do not touch eyes with contaminated body parts or materials. Have eye washing facilities readily available.
- Skin and body protection : Prevent contact with shoes and clothing. Use rubber apron and overshoes.
- Protective measures : Other equipment not normally required. Use professional judgment in the selection, care, and use.
- Engineering measures : Not required under normal conditions of use. Use local exhaust when the general ventilation is inadequate.

Exposure Limits

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Regulation</u>	<u>Limit</u>	<u>Form</u>
Vinyl acetate	108-05-4	ACGIH TWA:	10 ppm	
		ACGIH STEL:	15 ppm	

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

- Form : Liquid
- Color : Off-White to White
- Odor : None
- pH : 9.5
- Vapour pressure : Not available.
- Vapor density : Heavier than air
- Melting point/range : Not available.
- Freezing point : 32 F, 0 C
- Boiling point/range : 212 F, 100 C
- Water solubility : Soluble
- Specific Gravity : 1.1
- % Volatile Weight : 64.3 %

**TAMMSWELD - 55 GALLON DRUM**Version 2.
REVISION DATE: 09/24/2008

Print Date 09/26/2008

SECTION 10 - REACTIVITY / STABILITY

Substances to avoid : Strong acids.Strong bases.
 Stability : Stable
 Hazardous polymerization : Will not occur.

SECTION 11 - TOXICOLOGICAL INFORMATION

Ethylene glycol, CAS-No.: 107-21-1
 Acute oral toxicity (LD-50 oral) 6,140 mg/kg (Rat) 14,600 mg/kg (Mouse) 8,200 mg/kg (Guinea pig) 8,810 mg/kg (Dog)

Vinyl acetate, CAS-No.: 108-05-4
 Acute oral toxicity (LD-50 oral) 2,920 mg/kg (Rat) 1,613 mg/kg (Mouse)
 Acute inhalation toxicity (LC-50) 3,680 mg/l for 4 h (Rat) 5,150 mg/l for 4 h (Mouse) 21,800 mg/l for 4 h (Guinea pig) 8,800 mg/l for 4 h (Rabbit) 1,550 mg/l for 4 h (Mouse) 2,500 mg/l for 4 h (Rabbit) 6,215 mg/l for 4 h (Guinea pig) 2,511 mg/l for 4 h (Rabbit)

SECTION 12 - ECOLOGICAL INFORMATION

No Data Available

SECTION 13 - DISPOSAL CONSIDERATIONS

Disposal Method : Waste not regulated under RCRA. Dispose of in compliance with state and local regulations.

SECTION 14 - TRANSPORTATION / SHIPPING DATA

TDG / DOT Shipping Description:
 NOT REGULATED

SECTION 15 - REGULATORY INFORMATION**North American Inventories:**

All components are listed or exempt from the TSCA inventory.
 This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

U.S. Federal Regulations:

SARA 313 Components : Ethylene glycol 107-21-1
 Vinyl acetate 108-05-4

SARA 311/312 Hazards : Acute Health Hazard



TAMMSWELD - 55 GALLON DRUM

Version 2.
REVISION DATE: 09/24/2008

Print Date 09/26/2008

OSHA Hazardous Components :
Ethylene glycol 107-21-1
Vinyl acetate 108-05-4

OSHA Status: Considered : Irritant
hazardous based on the
following criteria:

OSHA Flammability : Not Regulated

Regulatory VOC (less water and
exempt solvent) : 68 g/l
VOC Method 310 : 1 %

U.S. State Regulations:

MASS RTK Components : Ethylene glycol 107-21-1
Vinyl acetate 108-05-4

Penn RTK Components : Water 7732-18-5
Ethylene-Vinyl Acetate Copolymer 24937-78-8
Ethylene glycol 107-21-1

NJ RTK Components : Water 7732-18-5
Ethylene-Vinyl Acetate Copolymer 24937-78-8
Ethylene glycol 107-21-1

WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm:
None known.

SECTION 16 - OTHER INFORMATION

HMIS Rating :

Health	1
Flammability	0
Reactivity	0
PPE	

0 = Minimum
1 = Slight
2 = Moderate
3 = Serious
4 = Severe

Further information:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

Prepared by: Rich Mikol

Legend

ACGIH - American Conference of Governmental Hygienists
CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act
DOT - Department of Transportation

PEL - Permissible Exposure Limit
RCRA - Resource Conservation and Recovery Act
RTK - Right To Know



TAMMSWELD - 55 GALLON DRUM

Version 2.

Print Date 09/26/2008

REVISION DATE: 09/24/2008

DSL - Domestic Substance List
EPA - Environmental Protection Agency
HMIS - Hazardous Materials Information System
IARC - International Agency for Research on Cancer
MSHA - Mine Safety Health Administration
NDSL - Non-Domestic Substance List
NIOSH - National Institute for Occupational Safety and Health
NTP - National Toxicology Program
OSHA - Occupational Safety and Health Administration

SARA - Superfund Amendments and Reauthorization Act
STEL - Short Term Exposure Limit
TLV - Threshold Limit Value
TSCA - Toxic Substances Control Act
TWA - Time Weighted Average
V - Volume
VOC - Volatile Organic Compound
WHMIS - Workplace Hazardous Materials Information System