



RELEASE

PRODUCT NAME

RELEASE

MANUFACTURER & DISTRIBUTOR
OF INDUSTRIAL CHEMICALS
1611 GUNN HIGHWAY
ODESSA, FLORIDA 33556
(813) 886-8811

PRODUCT DESCRIPTION

COLOR and CLEAR RELEASES contain a specially-formulated releasing agent that form a moisture barrier between the stamping tools and wet concrete facilitate the release of flexible tools. It is a dry shake material applied directly on top of the concrete, COLOR HARDENER, or THIN-CRETE prior to stamping. The colored releasing agent contains integrated iron oxide pigments to add color and depth to the stamped surface. The clear leaves no trace. For use on stamped concrete products only.

BENEFITS

COLOR and CLEAR RELEASES are a must on textured concrete, providing the barrier essential to prevent suction that detracts from a finished product, thus greatly reduces the need for touch-up. By using color release, a rich looking antique effect is achieved. There are various combinations of colors that will give the two-tone effect by accenting the highlights. The darker color applied on top of the color hardener recesses into grout lines and deeper textures.

APPLICATION PROCESS

PREPARATION: All surrounding areas should be protected from contamination by the dust created by the broadcast method of application. Visqueen is recommended for masking.

SLAB PREPARATION: After all color hardener is applied, complete troweling for a smooth, even finish, with no bleed water on the surface.

BROADCASTING PROCEDURE: Material is a dust hazard, use a dust mask to prevent inhalation. Before tossing release, empty half of the contents of a pail into a clean, dry container and aerate material to loosen any compaction before spreading onto surface. Apply lightly and evenly over area using a casting motion. Use caution in windy conditions. Two applications are normally required for uniform coverage. Twenty pounds will cover approximately 1000 ft².

FINISHING

After the concrete has set and dried, remove the excess color and prepare the surface for sealer by rinsing with a 10:1 solution of water to acid, followed by rinsing with fresh water from a garden hose. Take care not to wash off completely. Use a lighter, quicker rinsing action for the grout lines and deeper indentations. Removing most of the release from the high spots, and leaving more of the color in the deeper areas will enhance antique effect for a beautiful, more natural finish. After the concrete has been washed and dried thoroughly, use INCRETE CLEAR SEAL to protect the surface and seal color permanently. One gallon of clear seal will cover approximately 200-250 ft² per gallon, depend on usage and conditions.

PACKAGING

20 lb. box

COLORS

Available in Increte's 30 standard colors plus LIGHT and DARK GRAY; LIGHT and DARK BROWN and CLEAR.

Special colors can be matched by request (minimum order requirements apply)

SAFETY PRECAUTIONS

Irritant to eyes and skin, Do not swallow. If eye or skin contact is made, flush with water for 15 minutes. If swallowed, dilute with water. Wear rubber gloves and splash proof goggles.

WARRANTY

All recommendations, statements and technical data contained herein based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty, either expressed or implied. User shall rely on his own information and tests to determine suitability of the product for the intended use and user assumes all risk and liability resulting from his use of the product of this manufacturer which proves to be defective. Neither seller nor manufacturer shall be liable to the buyer or any third person having any injury, loss or damage directly or indirectly resulting from use of or inability to use the product. Recommendations or statements other than those contained in written agreement signed by an officer of the manufacturer shall not be binding upon the manufacturer or seller.

AVAILABILITY

Available through distributors or contact manufacturer.

IMPORTANT NOTICE

THESE PRODUCTS ARE SOLD SUBJECT ONLY TO THE EXPRESSED WARRANTIES CONTAINED HEREIN. ADDITIONAL WARRANTIES, EXPRESSED OR IMPLIED, AND ANY WARRANTY OF MERCHANT ABILITY IS HEREBY EXCLUDED. BUYER AGREES THAT SELLER ASSUMES NO LIABILITY FOR CONSEQUENTIAL DAMAGES OF ANY KIND, WHICH RESULT FROM THE USE OR MISUSE OF THE MERCHANDISE SOLD HEREUNDER. IN THE EVENT THAT THE BUYER PROVES THAT ANY GOODS RECEIVED DO NOT CONFORM TO THE SPECIFICATIONS AGREED TO BETWEEN THE PARTIES OR IF THE BUYER PROVES THAT SUCH GOODS WERE DEFECTIVELY MANUFACTURED. THE BUYER'S REMEDIES SHALL BE LIMITED TO EITHER THE RETURN OF THE GOODS AND REPAYMENT OF THE PURCHASE PRICE OR REPLACEMENT OF THE NON-CONFORMING GOODS AT THE OPTION OF THE SELLER. SUCH REMEDY BEING EXCLUSIVE OF ALL OTHERS AND THE SOLE REMEDY AVAILABLE TO THE BUYER, HEREBY EXPRESSLY WAIVES ANY CLAIM TO ADDITIONAL DAMAGES.