



STAIN-CRETE

PRODUCT NAME

STAIN-CRETE

Manufacturer & Distributor of
Industrial Chemicals
1611 Gunn Highway
Odessa, Florida 33556
(813) 886-8811

PRODUCT DESCRIPTION

STAIN-CRETE is a deep penetrating; acid-based stain that can be used to color old or new concrete that has cured for 14 to 28 days. STAIN-CRETE can also be used in conjunction with Increte Systems New-Crete, self leveling overlay system after New-Crete has cured 24 hours. Stain-Crete chemically reacts with cured concrete to provide a distinctive, permanent color with a subtly shaded marbled effect, similar to the aged appearance of natural stone. STAIN-CRETE's rich variegated finish will not peel, crack, chip, or fade. STAIN-CRETE provides a terrific custom look and is ideal for residential, commercial, or municipal applications, including all masonry surfaces, horizontal or vertical such as basement floors, garage floors, driveways, entryways, patios, pool decks, sidewalks, as well as restaurants, mall entrances, hotels, and showrooms. STAIN-CRETE is available in six additional pastel colors for interior use only. These six new pastel colors provide a new range of colors not previously achievable based on soluble mineral salts.

BENEFITS

- STAIN-CRETE provides a stain resistant surface that, once sealed, is impervious to salts and salt spray, alkali, ultraviolet rays, and abrasion.
- STAIN-CRETE is easy to maintain.
- STAIN-CRETE provides variegated appearances and long-lasting durability.

APPLICATION

Apply 2 coats of Increte STAIN-CRETE with an acid resistant pump sprayer to concrete that is at least 14 to 28 days old, of uniform appearance, dry, and clean from all materials that would prevent or limit penetration and reaction. Use glass or plastic containers and keep away from metal to avoid corrosion. Avoid excessive puddling. Permit stained work to dry evenly. Apply second coat (if desired) in the same manner after eight hours. After second coat has dried for at least eight hours, scrub off all residue and salts with a stiff brush and water, and flush with clean water. Control water runoff.

Product may be diluted with water for shade variations. If using a diluted mixture or if concrete does not accept stain well additional Muriatic acid may be added.

Coverage – STAIN-CRETE should cover 125-200 square ft. per gallon of stain for two coats.

MAINTENANCE

STAIN-CRETE surface is easy to maintain and can be cleaned by sweeping, washing with commercial floor cleaners, then polishing with a clean cloth or mop. For interior use, a periodic application of Increte Systems High Gloss Wax – floor wax will ease cleaning and add luster. To preserve the variegated appearance and provide long-lasting durability, apply Increte Systems CLEAR SEAL, a protective sealer containing UV inhibitors. Periodic reapplication of sealer is recommended when surfaces are subject to high pedestrian and vehicular traffic.

SAFETY PRECAUTIONS

CAUTION – Contains Hydrochloric Acid and soluble salts of heavy metals. Avoid contact with skin or eyes. Avoid breathing vapors. Do not drink. After handling or exposure, wash thoroughly. Use only with adequate ventilation. **KEEP AWAY FROM CHILDREN.**

External Antidote – Flood with water, then water containing baking soda.

Internal Antidote – Give water, milk, milk of magnesia, or egg whites beaten in water. Do not induce vomiting. Call Physician immediately.

AVAILABILITY

Available through distributors or contact manufacturer.

WARNING

The STAIN-CRETE colors Weathered Copper, Lime Green, and Bronze are to be used only for interior applications. They may react with water and blacken or darken when exposed to excessive moisture. When applying these colors the sub-grade must not be subject to hydrostatic pressure and must be well drained. The chemically stained concrete must be protected from any source of water. The pastel Stain-Crete colors are also for interior use only and should not be used for exterior applications. Fading may occur with the pastel colors due to UV degradation.

IMPORTANT NOTICE

THESE PRODUCTS ARE SOLD SUBJECT ONLY TO THE EXPRESSED WARRANTIES CONTAINED HEREIN. ADDITIONAL WARRANTIES, EXPRESSED OR IMPLIED, AND ANY WARRANTY OF MERCHANTABILITY IS HEREBY EXCLUDED. BUYER AGREES THAT SELLER ASSUMES NO LIABILITY FOR CONSEQUENTIAL DAMAGES OF ANY KIND, WHICH RESULT FROM THE USE OR MISUSE OF THE MERCHANDISE SOLD HEREUNDER. IN THE EVENT THAT THE BUYER PROVES THAT ANY GOODS RECEIVED DO NOT CONFORM TO THE SPECIFICATIONS AGREED TO BETWEEN THE PARTIES OR IF THE BUYER PROVES THAT SUCH GOODS WERE DEFECTIVELY MANUFACTURED. THE BUYER'S REMEDIES SHALL BE LIMITED TO EITHER THE RETURN OF THE GOODS AND REPAYMENT OF THE PURCHASE PRICE OR REPLACEMENT OF THE NON-CONFORMING GOODS AT THE OPTION OF THE SELLER. SUCH REMEDY BEING EXCLUSIVE OF ALL OTHERS AND THE SOLE REMEDY AVAILABLE TO THE BUYER, HEREBY EXPRESSLY WAIVES ANY CLAIM TO ADDITIONAL DAMAGES.

WARRANTY

All recommendations, statements and technical data contained herein based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty, either expressed or implied. User shall rely on his own information and tests to determine suitability of the product for the intended use and user assumes all risk and liability resulting from his use of the product of this manufacturer which proves to be defective. Neither seller nor manufacturer shall be liable to the buyer or any third person having any injury, loss or damage directly or indirectly resulting from use of or inability to use the product. Recommendations or statements other than those contained in written agreement signed by an officer of the manufacturer shall not be binding upon the manufacturer or seller.