



Insulation Board, Flotation Billets



Styrofoam
Brand Insulation



ASDCO stocks the following extruded polystyrene insulation (XPS) boards

Thickness	Board Size	Type	Strength
3/4"	48" x 96"	Dow TG (Tongue & Groove)	25 psi
1"	48" x 96"	Dow TG (Tongue & Groove)	25 psi
1-1/2"	48" x 96"	Dow SC (Score Board)	25 psi
2"	48" x 96"	Dow SC (Score Board)	25 psi
1"	24" x 96"	Dow HI-40	40 psi
2"	24" x 96"	Dow HI-40	40 psi


ASTM C-578 specifications for rigid cellular polystyrene thermal insulation

	Type X	Type IV	Type VI	Type VII	Type V
Min. density, lb/cuft	1.3	1.6	1.8	2.2	3.0
Min. compressive strength, psi	15	25	40	60	100
Min. flexural strength, psi	40	50	60	75	100
Min. thermal resistance per inch, R value	5.0	5.0	5.0	5.0	5.0
Max. water vapor permeance per inch, perms	1.1	1.1	1.1	1.1	1.1
Max. water absorption, volume %	0.3	0.3	0.3	0.3	0.3
Max. dimensional stability, change in %	2.0	2.0	2.0	2.0	2.0
Min. Oxygen index, volume %	24.0	24.0	24.0	24.0	24.0

We specialize in full-truck or part-truck shipments to your site!



Flotation Billets



**The most effective means of floating your dock or floating platform.
No other buoyancy product compares! Each cubic foot floats 55 lbs.!**

<u>Stock sizes</u>	<u>Float Capacity</u>	<u>Special order sizes</u>	<u>Float Capacity</u>
10" x 20" x 96"	611 lbs.	7" x 20" x 96"	427 lbs.
		10" x 24" x 96"	733 lbs.
		7" x 20" x 108"	481 lbs.
		10" x 20" x 108"	688 lbs.
		10" x 24" x 108"	825 lbs.

